

# KÜHTREIBER®

## KITin 150 TIG LA

10-150 A

140 A/60%



Code	50281
Input power 50/60 Hz [ V ]	1 x 230
Protection – slow [ A ]	16
Welding current range [ A ]	10 – 150
Duty cycle 100 % [ A ]	125
Duty cycle 60 % [ A ]	140
Duty cycle at max. I	45%
Mains current/inp. 60 % [ A/kVA ]	19/4.3
Open circuit voltage [ V ]	88
Ingress Protection	IP 23 S
Cable panel socket	10-25
Recommended type of torch	KTB 17V
Dimensions [ mm ]	220 x 143 x 310
Weight [ kg ]	5.5

### FEATURES

HOT START	●
ARC FORCE	●
ANTI STICK	●
V.R.D.	●
LIFT ARC	●
TIG PULS	●
FREQUENCY OF THE PULSATIION	●
DOWN SLOPE	●
END CURRENT	●
AAE	●
Strap belt for easy carrying	●

### OPTIONAL ACCESSORIES:

Welding cables	●
Plast. case for inverters and acces.	●
Remote control	●
Auto-darkening mask	●
Electrodes	●
Welding torch TIG	●

### DESCRIPTION

KITin 150 TIG LA is professional inverter welding machine of the third generation designed with the use of IGBT technology with the fast microprocessor regulation. Machine is noted with high duty cycle (125 A at 100%), performance and comfort controls.

The controls of machine are integrated in the new generation of keyboard that replaces the standard mechanical solutions. This increases the the reliability and precision of machine setup.

### USAGE

This is the right choice for the use in manufacturing, assembling, in metal production, by maintenance or at home.

