

KÜHTREIBER®

KIT 3000 STANDARD

30-250 A

210 A/60%



Code	51158
Input power 50/60 Hz [V]	3x400
Protection – slow [A]	16
Welding current range [A]	30 – 250
Output voltage range [V]	17.7 – 39.2
Duty cycle 100 % [A]	190 (at 40°C)
Duty cycle 60 % [A]	210
Duty cycle [A]	250 (45%)
Mains current/input 60 % [A/kVA]	9.6/7
Winging	Cu/Al
Number of adjustment points	10
Wire feed	4-roll
Standard equip roll	0.8 – 1.0
Wire feed speed [m/min]	1 – 20
Material of wire	
– Steel, Stainless steel	●
– Aluminium	●
– Cored wire	●
Ingress Protection	IP 21 S
Dimensions [mm]	902 × 510 × 890
Weight [kg]	75

FEATURES

2-STROKE / 4-STROKE ●

EASY USE ●

SPOT PULS ●

GENERATOR ●

TEST GAS ●

DESCRIPTION

KIT 3000 is professional welding machine equipped with a high-powered transformer, robust wire feeder with an efficient motor, EURO connector and electronic control.

The main advantages of machines KIT are excellent welding qualities, 10-grade voltage control, high power, high duty cycle, high reliability and easy operating.

USAGE

Machines are designed for medium and heavy-machinery production, maintenance plants and metal-production.

The machines are designed for plants with the highest levels of performance, reliability and simple control.

